

Case No. 21033

Permanent Magnet Actuating Mechanism

5 **Background of the Invention**

10 The present invention pertains to a permanent magnet actuating mechanism, and more particularly, to a permanent magnet motor that can be driven from a self-contained source of power.

15 There is a need for a relatively inexpensive, self-contained source of power for remote locations. Permanent magnet motors or generators are known in the art, see, for example, Pennington Patent No. 999,335; Busch Patent No. 3,665,227 and Clarke Patent No. 4,947,071. The Pennington patent shows a magneto generator having a plurality of cores, which are mounted on an annular ring secured to the casing. Carried on a shaft for rotation in the casing are a plurality of C-shaped magnets, the north-south axis of each being aligned with the longitudinal axis of each core. The Busch patent reveals a relatively complex design for an electric motor-generator that includes a shaft, a rotating member with snap-on coils, and magnetic members in a casing. The Clarke patent discloses a relatively complex high speed motor having horseshoe-shaped magnets mounted on a rotor and a plurality of stator electromagnets spaced apart about the rotor cavity of the motor. The stator is formed in two arrays, each of which includes pulling electromagnets and pushing electromagnets. The present invention is intended to simplify the design of a permanent magnet motor, to provide same with a self-contained power source, such as a battery, so that it can be used at remote locations, and to enhance the performance of existing designs in a straightforward manner.

25 In one aspect of the invention, the permanent magnet actuating device incorporates a stator with energizing coils, a member actuated thereby, a battery power source for energizing the energizing coils for actuating the member. Upon actuation of a control circuit, the member will be actuated. It is contemplated

30

that the member may be moved linearly, though in a presently preferred embodiment of the invention, the member is a rotor in a permanent magnet motor and is rotated for providing a rotary output. The rotor will be provided with a plurality of permanent magnets that cooperate with the energizing coils. In essence, the permanent magnet motor can drive an electrical generator for delivering power as needed at a remote site, for example, a microwave tower. In another aspect, it is contemplated that the permanent magnet motor can be employed to operate the electrical appliances in a home or business.

Summary of the Invention

The permanent magnet actuating mechanism comprises a frame upon which are mounted a plurality of energizable coils. A member is mounted for movement on the frame. A plurality of permanent magnets are mounted on the member. The axes of the energizable coils are disposed substantially at right angles to the axes of the permanent magnets. Upon energization of the energizable coils, the member is moved with respect to the frame. Such movement may be linear. A control is provided for energizing the energizable coils.

In another aspect of the invention, the permanent magnet actuating mechanism may be in the form of a permanent magnet motor comprising a frame mounting a plurality of energizable coils. A starting coil is mounted on the frame. A wheel is rotatably mounted on the frame. Carried on the wheel are a plurality of permanent magnets. The axes of the energizable coils are disposed substantially at right angles to axes of the permanent magnets. The permanent magnets cooperate with the energizable coils, whereby, upon energization of the starting coil, the wheel will begin to rotate in a first direction and upon energization of the energizable coils, the wheel will continue to rotate in the first direction. Preferably, the permanent magnets are equally spaced from one another on the wheel and the energizable coils are equally spaced from one another on the frame. In one specific embodiment of the invention there are four energizable coils and eight permanent magnets. A control arrangement is provided for selectively energizing the starting

coil and the energizing coils. The control arrangement includes a power source, for example, a battery.

5 An object of the present invention is to provide a relatively inexpensive source of power that can be used at remote locations that is self-contained and comprises a permanent magnet motor actuated from a battery.

10 Another object of the present invention is to provide a relatively inexpensive self-contained permanent magnet motor actuated from a battery that can be used to power a generating device.

15 Yet another object of the present invention is to provide a permanent magnet motor incorporating a stator with energizable coils and a rotor with a plurality of permanent magnets secured thereto, the axes of the energizable magnets being disposed at substantially right angles to the axes of the permanent magnets.

20 A further object of the present invention is to provide a permanent magnet motor having a stator with equidistantly spaced energizable coils and a rotor with a plurality of permanent magnets secured thereto, the outer surfaces of the permanent magnets being constructed and arranged to be complementary to the exterior surfaces of the energizable coils, whereby the outer surface of each permanent magnet passes closely to the outer surface of an energizable coil during rotation of the rotor.

25 Other objects and advantages of the present invention will be made more apparent hereinafter.

Brief Description of the Drawing

There is shown in the attached drawing a presently preferred embodiment of the present invention, wherein like numbers in the various views refer to like element and wherein:

Fig. 1 is a perspective view of a permanent magnet motor embodying the present invention;

Fig. 2 is a perspective view of the permanent magnet motor of Fig. 1, with parts broken away;

Fig. 3 is an exploded perspective view of the permanent magnet motor of Fig. 1;

Fig. 4 is a front perspective view of the permanent magnet motor, with parts broken away;

Fig. 5 is a side elevational view of the permanent magnet motor of Fig. 1;

Fig. 6 is a control circuit schematic for the permanent magnet motor;

Fig. 7 illustrates schematically the orientation of a permanent magnet on the wheel with a associated energizable coil on the frame in a first position prior to energization of the energizable coil;

Fig. 8 illustrates schematically the orientation of a permanent magnet with an associated energizable coil, upon energization of the energizable coil.

Fig. 9 illustrates schematically the orientation of a permanent magnet with respect to an associated energizable coil during continued rotation from the position shown in Fig. 8; and

Fig. 10 illustrates schematically the orientation of a permanent magnet with respect to an associated energizable coil upon deenergization of the energizable coil and further rotation of the permanent magnet from the position shown in Fig. 9.

Detailed Description of the Invention

There is shown in Figs. 1-5 a presently preferred embodiment of the present invention. The permanent magnet motor 10 comprises a frame 12 having uprights 14, 15, 16 at each end, which are interconnected by outer struts 18,20, intermediate strut 19, and cross strut 22, 24, 26. The struts may be made from a suitable material, such as aluminum. Corners 30 each connect an upright, an outer strut and a cross strut, for example, the lower right corner 30 in Fig. 1 connects the cross strut 22, the upright 16 and the lower outer strut 20. The openings in the corners for receiving the various frame members are substantially at right angles to one another. Connectors 40 secure the cross struts with the intermediate upright 15 and the intermediate strut 19. The connectors 40 are provided with aligned openings for receiving cross struts and openings at substantially right angles for receiving the intermediate upright 15 and the intermediate strut 19. Upper longitudinal brace 36 and lower longitudinal brace 38 help to rigidify the frame 12. The upper and lower braces 36 and 38, respectively, may be fabricated from stainless steel and are in the form of angles. Suitable fasteners, for example, bolt and nuts 41,43 are provided to secure the upper and lower braces 36 and 38 to the upright 14 and 16.

Bearings 44,45 are secured to the upper and lower braces 36 and 38 by suitable fastening means, for example, bolts 47 and nuts 49, for rotatably supporting the shaft or axle 46 of the wheel 48. Equidistantly spaced on the frame

12 are four energizable coils 52a, 52b, 52c, and 52d. The energizable coils each comprise a dumbbell-like core of reduced diameter with, wire wound on the center portion between the enlarged diameter ends. The energizable coils have, in general, the exterior appearance of cylinders. The energizable coils 52a, 52b, 52c, and 52d are connected to the frame 12 by core fastener means, which may be in the form of angle brackets 56 secured on the one side to an end to the core of an energizable coil and the other side of a part of the frame 12. For example, as seen in Figs. 1 and 2, there is a bracket 56 at each end of the energizable coil 52b. The brackets 56 are secured to the upright 15 by suitable fastening means, for example, bolts and nuts 58,59 and to the core of the energizable coil 52b by screws 53, or like fasteners.

Secured to the top of the frame 12 are supports 60 that are connected to the struts 18, 19, and 20 by suitable fastening means, for example, bolts 62 and nuts 63. Mounted on the supports 60 are heat sinks 64 and solid state relays 102,104,106,108. As shown in Figs. 1 and 2, four heat sinks 64 are used in the preferred embodiment of the invention, though it will be understood that different numbers of heat sinks may be used, depending upon the application. The heat sinks 64 are operative to cool the controller in the control means, as will be discussed hereinafter. The operation of the solid state relays will also be discussed hereinafter.

A starting coil 66 is disposed on the frame 12 adjacent the wheel 48. The starting coil 66 may be carried on the lower intermediate strut 19 by angle brackets 68, which may be secured to the strut 19 by suitable fastening means, for example, bolts and nuts 70, 71. As will be more fully explained hereinafter, the starting coil 66 will be energized to start the wheel 48 rotating in a first direction, for example, clockwise.

The wheel 48 comprises a central support or inner stabilizer ring 72, outer stabilizer rings 74 and 76, and wheel covers 78, 80. Inner torque ring 73 is suitably secured to the shaft 46, for example, the inner torque ring 73 may be keyed to the shaft 46. The shaft 46 is drivingly engages within complementary openings

82, 84 in the wheel covers 78, 80. Secured equidistantly about the wheel 48 are a plurality of permanent magnets. In the embodiment illustrated there are eight permanent magnets 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h. The permanent magnets 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h are each held between stabilizer blocks 88 that are secured to the central support 72 of the wheel 48 by bolts 90. As more clearly shown in Fig. 3 there are two bolts 90 for securing each stabilizer bar 88 to the central support or inner stabilizer ring 72.

The permanent magnets 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h each have a recessed outer surface 92 that is complementary in shape and size to the outer configuration of the energizable coils 52a, 52b, 52c, and 52d. In use, the outer surface of each permanent magnet 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h passes closely to the outer surface of an energizable coil 52a, 52b, 52c and 52d during rotation of the wheel 48 for enhancing the magnetic field strength.

A feature of the present invention is that the axes of the energizable coils 52a, 52b, 52c, and 52d are disposed substantially at right angles to the axes of the permanent magnets 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h. The permanent magnet 86a, 86b, 86c, 86d, 86e, 86f, 86g and 86h are preferably made from a material such as Neodymium.

A proximity switch 93 is carried on bracket 96 secured to the cross braces 36 and 38 of the frame 12. The proximity switch 93 cooperates with the flags 97 on the wheel cover 78. Preferably, the number of flags is equal to the number of permanent magnets and the flags 97 are positioned on the wheel cover 78 corresponding to the position of the associated permanent magnet. In the instant example, there are eight flags 97 suitably affixed on the wheel cover 78. The proximity switch 93 senses the flags 97 during rotation of the wheel 48 for sending a signal to energize the energizing coils 52a, 52b, 52c, and 52d. The energizable coils 52a, 52b, 52c, and 52d are energized or turned on when the proximity switch 93 senses a flag 97 and is deenergized or turned off when the proximity switch 93

no longer senses a flag 97. The function of the proximity switch 94 will be explained later in connection with the explanation of the control means.

Control means are provided for selectively and sequentially energizing the starting coil 66 and the energizing coils 52a, 52b, 52c, and 52d. With reference to Fig. 6, the control means includes a controller 100, and solid state relays 102, 104, 106, 108 and 110 in communication therewith. The solid state relay 102 is connected to the starting coil 66. The solid state relays 104, 106, 108 and 110, respectively, are connected to the energizing coils 52a, 52b, 52c, and 52d, respectively. A power supply 112 is operatively connected to the controller 100. Preferably, the power supply 112 comprises a 24 volt DC battery, though it will be apparent to persons skilled in the art that other size batteries or other power sources may be used. An on/off switch 114 is provided to turn the permanent magnet motor 10 on and off. Also in the control means in circuit with the controller 100 are the proximity switches 93 and 94 and RPM gauge 120. Basically, when the switch 114 is turned on, the starting coil 66 is energized to initiate rotation of the wheel 48 in a first direction. Then the energizing coils 52a, 52b, 52c, and 52d are energized in order to continue the rotation of the wheel 48. Energization and deenergization of the energizable coils 52a, 52b, 52c, and 52d is accomplished by the proximity switch 93 sensing a flag 97 and sending an appropriate signal to the controller 100 to turn the energizable coils on and off. The energizable coils 52a, 52b, 52c, and 52d are turned on and off together. The proximity switch 94 senses the RPM of the shaft 46 and displays same on the RPM gauge 120.

The power supply 112 is in circuit with a generator 136 via lines 138 and 139. The generator shaft 137 is suitably connected to the shaft 46 of the permanent magnet motor 10 for driving the generator 136 to provide power for recharging the battery 112. The connection between the shaft 46 of the permanent magnet motor 10 and the shaft 137 of the generator 136 can be a suitable mechanical connection, for example, a belt or chain. Excess capacity of power from the generator 136 can be used to power other devices, as needed, as would be apparent to persons skilled in the art.

Turning now to Figs. 7, 8, 9, and 10 there is shown schematically the operation of a permanent magnet 86a with respect to an energizable coil 52a. In Fig. 7, the energizable coil 52a is deenergized or off. The permanent magnet 86a is attracted toward the core of the energizable coil 52a as indicated by the attraction force line extending from the positive of the permanent magnet 86a toward the positive of the energizable coil 52a. In Fig. 8. The energizable coil is shown energized or on. As the permanent magnet 86a approaches the energizable coil 52a as shown in Fig. 8, there are both attraction and repulsion forces. The repulsion force is indicated by the force lines extending between the positive of the permanent magnet 86a and the positive of the energizable coil 52a. The attraction force is indicated by the force lines extending from the positive of the permanent magnet to the negative of the energizable coil 52a. At the instant represented in Fig. 8, the attraction force and the repulsion force is about equal.

In Fig. 9 the energizable coil 52a is still energized or on. The attraction force is significantly larger than the repulsion force and the permanent magnet 86a is urged clockwise as indicated by the rotation arrow in Fig. 9. The axis of the permanent magnet 86a is at substantially right angles to the axis of the energizable coil 52a. This feature of the invention enhances the magnetic force between the permanent magnet 86a and the energizable coil 52a. The magnetic force between each of the permanent magnets and an associated energizable coil is further enhanced by the close association of the curved recess 92 defined in the outer surface of each permanent magnet with the complementary exterior surface of each energizable coil. The energizable coil 52a, which is representative of each of the energizable coils, includes a core comprising a center portion 130 of reduced diameter and ends 132 of enlarged diameter. Wire 134 is wound on the center portion 130 of the core between the ends 132. In a presently preferred embodiment 10 gage wire is used.

Fig. 10 shows the orientation of the permanent magnet 86a after continued rotation following deenergization of the energizing coil 52a. It will be understood that the operation described in Figs. 7-10 will be repeated as each

permanent magnet cooperates with a successive energizing coil during rotation of the wheel 48 in the frame 12.

5 The energizing coils 52a, 52b, 52c and 52d will be energized sequentially during operation by the cooperation of the proximity switch 93 on the frame 12 and the flags 97 on the wheel 48. As noted above, the flags 97 are affixed to the wheel cover 78 of the wheel 48 in alignment with an associated permanent magnet. In the embodiment shown in Figs. 1 and 2, for example, there is a flag associated with each permanent magnet. Thus, there are eight flags 97 and eight
10 permanent magnets 86a, 86b, 86c, 86d, 86e, 86f, 86g, and 86h. When a flag 97 is sensed by the proximity switch 93, the energizing coils will be energized through the operation of the controller 100 and associated solid state relay. The energizing coils will be energized during the time that a flag 97 is sensed by the proximity switch 93. For example, assume that the proximity switch 93 senses a flag 97 and
15 sends a signal to the controller 100. The controller 100 will actuate the appropriate solid state relays 104, 106, 108, and 110 and the energizable coils 52a, 52b, 52c, and 52d, respectively, associated with the solid state relays 104, 106, 108 and 110, respectively.

20 There has been provided by the present invention an improved permanent magnet motor that incorporates a power source so that it can be employed at remote locations where power might otherwise not be available. The improved permanent magnet motor uniquely includes a stator on the frame and permanent magnets on the rotor or wheel, wherein the axes of the permanent
25 magnets and the energizable coils are at substantially right angles to one another. Further, the outer surface of the permanent magnets are contoured complementary to the exterior surface of the energizable coils so that the permanent magnets and the energizable coils can cooperate closely during rotation of the permanent magnets on the wheel with respect to the energizable coils on the frame.

30 Other arrangements of permanent magnets and energizable coils are permissible within the scope of the present invention. For example, instead of eight

permanent magnets on the wheel or rotor, four permanent magnets are used in a prototype model of the permanent magnet motor. Further, the energizable coils and the support for the permanent magnets could be constructed and arranged linearly, whereby, upon energization of the energizable coils the support would move linearly.

5

Though I have shown a presently preferred embodiment of the present invention, it will be understood by person skilled in the art that the invention may be otherwise embodied within the scope of the following claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205